HOSOKAWA OPTISIZER IN-PROCESS PARTICLE SIZING









Mineral

Metals

for Performance Improvement

A new, dry powder, in-process particle sizing system available from Hosokawa Micron offers high performance accuracy within an easy to use and compact unit that costs a fraction of other systems available on the market. Using established laser diffraction technology from Xoptix the Optisizer presents fast, reliable, reproducible and easy to understand and interpret particle size distribution data. The ability to measure particle size distribution during the production process allows engineers to quickly assess the effects of any process change on the finished product. The Optisizer allows data to be automatically fed to the plant and control system to allow for optimum process control. measurements contaminants **BENEFITS OF IN-PROCESS PARTICLE SIZING** Optimise process stability

IN-PROCESS V MANUAL SAMPLING

- Operator error associated with manual sampling is eliminated
- In-process delivers real time
- Closed system eliminates dust

- Maximise product throughput
- Easy to troubleshoot
- Reduce energy consumption
- Reduce waste/reject product





OPTISIZER IN-PROCESS PARTICLE SIZING

Manufactured using high stability lasers, the best optics and the highest spec detectors the Hosokawa Optisizer is a true laser diffraction instrument built to ISO13320 to give the high levels of accuracy of a laboratory instrument. Built within a robust and ruggedised frame the Optisizer gives stable measurements even under extreme conditions.

HOW IT WORKS

Sample is diverted from the main product flow passing through the sizing cell and back into the main process stream. Laser light scattered from the particles is collected by the detector and transferred to the computer where the size is calculated. Thus the sample measurement is real time, allowing product quality changes to be made with minimum product wastage.

FEATURES

- Unique cell cleaning system
- Remote monitoring up to 2km
- Fully user configurable software
- Outputs to external process control
- IP65 protected



STANDARD MODULES

There are three standard modules:

XO01P

For measuring particles conveyed in air from 0.5 to 220 microns

XO02P

For measuring particles conveyed in air from 1.2 to 550 microns


XOUSE

For measuring particles conveyed in air from 2.5 to 1100 microns


NON-STANDARD APPLICATIONS

ATEX options available

Stack and extend size extension facility. Two Optisizers with covering different particle size ranges may be stacked on top of each other which means that very wide size ranges can be measured with a resolution not possible from any other system.



HOSOKAWA MICRON



Hosokawa Micron Ltd Rivington Road, Whitehouse Industrial Estate Runcorn, Cheshire, England, WA7 3DS Tel: +44 (0) 1928 755100 Fax: +44 (0) 1928 714325

e.mail: info@hmluk.hosokawa.com Visit our website at: www.hosokawa.co.uk The Hosokawa Micron Group will always be the leading global company covering the mountain range of Powder Technologies. The Group will achieve peaks of excellence in the development and commercialisation of advanced materials, process equipment and systems engineering.

Hosokawa Alpine AG
Peter Dörfler-Str. 13-25
DE – 86199 Augsburg, Germany
Tel: +49 (0)821-59 06 – 0
Fax: +49 (0)821-59 06 – 101

Email: mail@alpine.hosokawa.com Visit our website at: www.alpinehosokawa.com